



P.C.B LAYOUT

SPECIFICATIONS (技术参数)

Current Rating (额定电流): 3.0 Amps

Contact Resistance (接触电阻): 30mΩ Max

Insulator Resistance (绝缘电阻): 1000 MΩ min.

Dielectric Withstanding (耐压值): AC 600V/minute

Operating Temperature (工作温度): -40°C +105°C



JSD FH XX X X X XX X X X XXX X

- Brand 品牌
- Ejector Header 筒牛插座
- Pitch 间距 (Unit:mm)
10=1.00 12=1.27
20=2.00 25=2.54
- Ear height 耳朵高度 (Unit: mm)
A=4.35
B=8.00
- Grooving direction 开槽方向
0=In the middle (中间)
1=On both sides of the (两边)
- Add an insulator 添加绝缘体
0=There is no (没有)
1=There are (有)
- Material Type 塑胶体材质
0=PBT 3=PA9T
1=PA46 4=LCP
2=PA6T
- Contact Plated 镀层
0=Tin 锡 3=Gold 1.5U金 6=Gold 5U金
1=Gold 0.8U金 4=Gold 2U金 7=Gold 10U金
2=Gold 1.0U金 5=Gold 3U金 8=Gold 15U金
- Mounting Style 安装方式
S=Straight DIP Type 180度直插板
R=Right Angle DIP Type 90度插板
M=SMT vertical stick Type 立贴板
- Number of contacts 触点总数
Double row=06 to 140Pin
- Locate the column (定位柱)
0=No fixed 没有固定
1=Have a fixed 有固定
- Pin length 针的总长度

No. of Contacts	A	B	C
10	31.90	21.84	10.16
14	36.98	26.92	15.24
16	39.52	29.46	17.78
20	44.60	34.54	22.86
26	52.22	42.16	30.48
30	57.30	47.24	35.56
34	62.38	52.32	40.64
40	70.00	59.94	48.26
50	82.70	72.64	60.96
60	95.40	85.34	73.66
64	100.48	90.42	78.74

客户料号:	无	Units	mm	Scale	Drawing By	Date
客户规格:	无	Tolerance Unless Otherwise Specified			2015年12月24日	
注:		.X	~	±0.30	1 of 1	Title
		.XX	~	±0.30	Third Angle Projection	
		.XXX	~	±0.30		
REV	ECN.NO.	Angle	~	±0.30		



深圳市精时代电子科技有限公司
 官网: www.jsdconn.com
 电话: 0755-33583386/33583396
 传真: 0755-33583356

平面设计	2.54牛角90度弯插高低卡位系列	
张火新	Drawing No.	JSDEH25X0XXXXXXX-001
18824345453	F/Name	B